

QwickBuild® Product Catalog

Deck framing system





A100 Profiles

www.outdure.com
















A194-10-28
Post Profile
90 X 90 X 2800mm

Material: Aluminium 6063-T6 Powder Coated - Black



A195-20-58
Post Profile

135 X 135 X 5800mm

Material: Aluminium 6063-T6 Powder Coated - Black



A200 Brackets & Components

For all profiles excluding A100 & A110 www.outdure.com



ALL.QB.BR.90.304.10X



ALL.QB.BRACLEATF.10X



ALL.QB.BR.JA.304.25X (A204-25X)



ALL.QB.JO.DJB.20X (A206-20X)



ALL.QB.JO.DJB.FLAT.20X (A207-20X)








A210 **Bracket A** For Beam to A194 Post 90 X 90

Material: Aluminum 6063-T6 Powder Coated - Black





A212 **Bracket Kit**

135 X 135

Material: Aluminum 6063-T6 Powder Coated - Black

For Beam to A195 Post





A300 Brackets

For A110 profiles www.outdure.com




ALL.QB.BR.90.28.10X



ALL.QB.BCF.28.10X







A400 Fasteners

www.outdure.com

A401-50X

Self-drilling screw 16mm



Included with most components

Length: 16mm, Head: Hex, Driver: 3/8" Material: SS304 Electrophoresis - Black

ALL.SC.QB-H16

A402-50X

Self-drilling screw 30mm



With a coarse thread for wood

Length: 30mm, Head: Hex, Driver: 3/8" Material: SS304 Electrophoresis - Black

A403-50X

Type 17 screw 65mm



With a coarse thread for wood

Length: 65mm, Head: Hex, Driver: 3/8" Material: SS304 Electrophoresis - Black

ALLSC.QB-H65

A404-50X

Type 17 screw 130mm



With a coarse thread primarily for solid blocking (railing)

Length: 130mm, Head: Hex, Driver: 3/8" Included: Washer. Material: SS304 Electrophoresis - Black

A409-50X



Self-drilling screw 20mm

For securing A510-A580 TwistClips in channel &/or in to control board expansion/contraction

Length: 20mm, Head: CSK, Driver: Torx 15 Material: SS304 Electrophoresis - Black

ALL SC OB-C20-7

A410-10X





For QwickBuild connections, typically bearer to post

Length: 90mm, Thread Diameter: 12mm, Head: Hex Material: SS304. Included: 1X Locking Nut, 2X Washers

A411-10X

M12 Bolt 12 X 140mm



For QwickBuild connections, typically bearer to post

Length: (6") 140mm, Thread Diameter: (1/2") 12mm, Head: Hex Material: SS304. Included: 1X Locking Nut, 2X Washers

A412-10X

M12 Bolt 12 X 180mm



For QwickBuild connections, typically bearer to post

Length: (8") 180mm, Thread Diameter: (1/2") 12mm, Head: Hex Material: SS304. Included: 1X Locking Nut, 2X Washers

A413-10X

M12 Bolt 12 X 230mm



For QwickBuild connections, typically bearer to post

Length: 230mm, Thread Diameter: 12mm, Head: Hex Material: SS304. Included: 1X Locking Nut, 2X Washers

A420

Driver Pack

Hex 3/8" Length: 80mm Hex 3/8" Length: 50mm

Torx 20 - 2x

Torx 15 - 2x

ALL.QB.DRIVER.PACK1



A500 Composite Board Fixings

To A100 profiles www.outdure.com





ALL.QB.QC.T06H.23.50X



A520-50X **TwistClip** Hidden fixings to interlock QwickBuild joist with: Trex Transcend, TimberTech Azek Reserve, TimberTech Terrain, TimberTech Vintage Gap: 6mm Material: Polypropylene - Black Included: A409-50X Screws

ALL.QB.QC.T06.24.50X-TX





Please test to ensure effective fit & function of TwistClips. Outdure can not take responsibility for any variances in board dimensions manufactured by other brands. Refer to Outdure's online QwickBuild catalog for updates.

ALL.QB.QC.06-50X







A600 Hardwood Board Fixings

To A100 profiles www.outdure.com

A610-50X

Screw for Hardwood - T20

36mm

Self-drilling screw for fixing hardwood timber boards, of thickness: 18 - 24mm to QwickBuild joists

Length: 36mm, Head: CSK Head Diameter: 9mm, Driver: Torx 20. Material: SS304

ALL.SC.QB-C36-9

A611-50X

Screw for Hardwood - H4

36mm

Self-drilling screw for fixing hardwood timber boards, of thickness: 18 - 24mm to QwickBuild joists

Length: 36mm, Head: CSK

Head Diameter: 12mm, Driver: H4. Material: SS304

ALL.SC.QB-C36-12

A620-50X

Screw for Hardwood - T20

45mm

Self-drilling screw for fixing hardwood timber boards, of thickness: 24 - 40mm to QwickBuild joists

Length: 45mm, Head: CSK Head Diameter: 9mm, Driver: Torx 20. Material: SS304

A621-50X

Screw for Hardwood - H4

45mm

Self-drilling screw for fixing hardwood timber boards, of thickness: 24 - 40mm to QwickBuild joists

Length: 45mm, Head: CSK


Head Diameter: 12mm, Driver: H4. Material: SS304

ALLSC.QB-C45-9 ALLSC.QB-C45-12



A700 Tile Fixings & Components

To A100 profiles www.outdure.com



A702-25X
Tile Retainer Bracket

Retains perimeter tiles
Install retainer brackets at ends of joists
that are perpendicular to edge of deck


Material: SS304 Electrophoresis - Black
Included: A401-50X Screws

ALL.QB.TI.RET.BR.25X



ALL.QB.TI.RET.SN.25X





ALL.QB.TI.SPS5MM.25X




ALL.QB.BR.TRIM180-45.10X



A800 Turf Fixings & Components

www.outdure.com



ALL.QB.QF.138X08X2.8


A810-50X

Screw for Turf 20_{mm}

Self-drilling screw for fixing turf to A801 baseboards

Length: (3/4") 20mm, Head: Flat, Driver: Philips Material: SS304 Electrophoresis - Black

ALL.SC.QB-F20



Screw for Turf Baseboards 30mm

Self-drilling screw for fixing A801 baseboards to QwickBuild joists

Length: 30mm, Head: Flat, Driver: Philips Material: SS304 Electrophoresis - Black



ALL.QB.QC.T06T.23.50X

A800 Additional Solutions



ALL.QB.QG.138X23X2.8.B




Solid Blocking



ALL.QB.QG.138X23X2.8.S

Batten





A855-10-28

45 X 33 X 2800mm

Universal plastic composite batten that facilitates top-down fixing of decking boards Material: Recycled HDPE











A910-10X

Deck Support Adjustable

Height-adjustable range: 35 - 65mm

Stack A915 under A910: 8X maximum Material: Polypropylene - Black. Included: Protection Pad



A915-10X

Deck Support Extender

Height: 30mm

Stack A915 under A910: 8X maximum Material: Polypropylene - Black

A920-10X

Deck Support Slope Corrector - Up to 7%




Height:

Optional item - Stacks under A910 Material: Polypropylene - Black

A925-10X

Deck Support Protection Pad - Acoustic



Height:

Optional item - Stacks under A910 Material: Rubber